

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : iLAST GAS TREATMENT 12 FL.OZ.  
 Product code : FPI0009

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fuel Additive

#### 1.3. Details of the supplier of the safety data sheet

US Global Petroleum  
 9101 Fullerton Avenue  
 Franklin Park, IL 60131 - USA  
 T 773-376-9660

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
 Asp. Tox. 1 H304

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
 Hazard statements (GHS-US) : H227 - Combustible liquid  
 H304 - May be fatal if swallowed and enters airways  
 Precautionary statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
 P280 - Wear protective gloves, protective clothing, eye protection, face protection  
 P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
 P331 - Do NOT induce vomiting  
 P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
 P403+P235 - Store in a well-ventilated place. Keep cool  
 P405 - Store locked up  
 P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	>= 95	Asp. Tox. 1, H304
Naphtha, Hydrotreated Heavy	(CAS No) 64742-48-9	0.104-0.972	Asp. Tox. 1, H304
Paraffins (Petroleum), Normal C5-20	(CAS No) 64771-72-8	< 1	Not classified
Xylene, Mixture of Isomers	(CAS No) 1330-20-7	< 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Ethylbenzene	(CAS No) 100-41-4	< 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice. Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin.
- Symptoms/injuries after eye contact : Irritation of the eye tissue. May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Explosion hazard : May form flammable/explosive vapor-air mixture.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Obtain special instructions. Do not handle until all safety precautions have been read and understood. Eliminate all ignition sources if safe to do so.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. Use only non-sparking tools. The floor of the depot should be impermeable and designed to form a water-tight basin. Provide local exhaust or general room ventilation. Ground/bond container and receiving equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ethylbenzene (100-41-4)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	125 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100
USA OSHA	OSHA PEL (STEL) (mg/m <sup>3</sup> )	545 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (STEL) (ppm)	125 ppm

Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours

### 8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods. Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear respiratory protection.
- Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colourless to light yellow.
- Odor : Characteristic.

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 148 - 198 °C (Lowest Component)
Flash point	: 85 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 0.1 PSIA @ 100 deg F
Relative vapor density at 20 °C	: No data available
Relative density	: 0.803
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 1.92 cSt @ 40 Deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content : < 1 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
LD50 oral rat	3523 - 8600 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; 3523 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value; >4000 mg/kg bodyweight; Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 4200.000000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	29 mg/l/4h (Rat; Experimental value; 27.57 mg/l/4h; Rat; Experimental value)
<b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>	
LD50 oral rat	> 5000 mg/kg (Rat)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit)

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B

<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
IARC group	3
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue. May cause slight eye irritation . Redness of the eye tissue. Inflammation/damage of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Ethylbenzene (100-41-4)</b>	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)

### 12.2. Persistence and degradability

<b>iLAST GAS TREATMENT 12 FL.OZ.</b>	
Persistence and degradability	Not established.
<b>Ethylbenzene (100-41-4)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O <sub>2</sub> /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O <sub>2</sub> /g substance
ThOD	3.17 g O <sub>2</sub> /g substance
BOD (% of ThOD)	45.4 (20 days)
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photolysis in the air.
<b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>	
Persistence and degradability	Readily biodegradable in water.
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Persistence and degradability	Not established.
<b>Naphtha, Hydrotreated Heavy (64742-48-9)</b>	
Persistence and degradability	Not established.
<b>12.3. Bioaccumulative potential</b>	
<b>iLAST GAS TREATMENT 12 FL.OZ.</b>	
Bioaccumulative potential	Not established.
<b>Ethylbenzene (100-41-4)</b>	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ethylbenzene (100-41-4)</b>	
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
BCF fish 2	7 - 26 (BCF; 8 weeks; Oncorhynchus mykiss; Flow-through system; Fresh water)
Log Pow	3.2 (Conclusion by analogy; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Paraffins (Petroleum), Normal C5-20 (64771-72-8)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Bioaccumulative potential	Not established.
<b>Naphtha, Hydrotreated Heavy (64742-48-9)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

<b>Ethylbenzene (100-41-4)</b>	
Surface tension	0.029 N/m
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): NA1993, Combustible liquid, n.o.s. (Petroleum Distillates), 3, III, Limited Quantity

ICAO/IATA (air): Not regulated,

IMO/IMDG (water): Not regulated,

Special Provisions: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)  
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s. (Petroleum Distillates)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672) T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>iLAST GAS TREATMENT 12 FL.OZ.</b>	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
<b>Ethylbenzene (100-41-4)</b>	
Subject to reporting requirements of United States SARA Section 313 Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
<b>Xylene, Mixture of Isomers (1330-20-7)</b>	
SARA Section 311/312 Hazard Classes	Fire hazard
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

### 15.2. International regulations

#### CANADA

<b>iLAST GAS TREATMENT 12 FL.OZ.</b>	
WHMIS Classification	Class B Division 3 - Combustible Liquid
<b>Ethylbenzene (100-41-4)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Distillates, Hydrotreated Light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid
<b>Distillates (Petroleum), Hydrotreated Light (64742-47-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

### EU-Regulations

No additional information available

# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Muta.Cat.2; R46

Full text of R-phrases: see section 16

### 15.2.2. National regulations

#### Ethylbenzene (100-41-4)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

### 15.3. US State regulations

#### iLAST GAS TREATMENT 12 FL.OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - California - Proposition 65

#### Ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	

#### Distillates, Hydrotreated Light (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Xylene, Mixture of Isomers (1330-20-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Paraffins (Petroleum), Normal C5-20 (64771-72-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Naphtha, Hydrotreated Heavy (64742-48-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)



# iLAST GAS TREATMENT 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Naphtha, Hydrotreated Heavy (64742-48-9)</b>			
No	No	No	No

<b>Ethylbenzene (100-41-4)</b>
<b>State or local regulations</b>

U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - California - Proposition 65

### SECTION 16: Other information

Other information : None.


Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H332	Harmful if inhaled
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



**HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*