

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : iLAST POWER STEERING FLUID 12 FL.OZ.
 Product code : FPI0008
 Other means of identification : This product is not hazardous in accordance with US OSHA 29CFR1910.1200 (Hazcom 2012), Canada Hazardous Products Regulations (WHMIS 2015) and the Globally Harmonized System (GHS).

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Power Steering Fluid

1.3. Details of the supplier of the safety data sheet

US Global Petroleum
 9101 Fullerton Avenue
 Franklin Park, IL 60131 - USA
 T 773-376-9660

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS No) 64742-52-5	>= 95	Asp. Tox. 1, H304
2-(2-Butoxyethoxy) Ethanol	(CAS No) 112-34-5	1 - 5	Eye Irrit. 2A, H319
Dipropylene Glycol Monomethyl Ether	(CAS No) 34590-94-8	< 1	Flam. Liq. 4, H227
White Mineral Oil (Petroleum)	(CAS No) 8042-47-5	0.03 - 0.06	Asp. Tox. 1, H304
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based	(CAS No) 72623-86-0	0.03 - 0.06	Not classified
Paraffinum Liquidum	(CAS No) 8012-95-1	0.03 - 0.06	Not classified
2,6-Di-tert-butylphenol	(CAS No) 128-39-2	0.001 - 0.0049	Not classified
Dibutyl Phosphonate	(CAS No) 1809-19-4	0.001 - 0.0049	Acute Tox. 4 (Dermal), H312
Tri-para-cresylphosphate	(CAS No) 78-32-0	0.001 - 0.0049	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Aquatic Chronic 2, H411
Petroleum Naphtha	(CAS No) 64742-47-8	< 1	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Toluene	(CAS No) 108-88-3	0.0001 - 0.0009	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

The exact percentage is a trade secret.

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Insufficient data available on direct fire hazard (flashpoint > 200°C).
-------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources.
------------------	----------------------------

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
-------------------------------	---

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Remove contaminated clothes. Wash contaminated clothing before reuse. Always wash hands after handling the product. Wash affected areas thoroughly after handling. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ MIST 8 HOURS
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ MIST 8 HOURS
2-(2-Butoxyethoxy) Ethanol (112-34-5)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm (Diethylene glycol monobutyl ether; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction and vapor)
Dipropylene Glycol Monomethyl Ether (34590-94-8)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm (2-Methoxymethylethoxy)propanol(DPGME); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value
USA ACGIH	ACGIH STEL (ppm)	150 ppm (2-Methoxymethylethoxy)propanol(DPGME); USA; Short time value; TLV - Adopted Value
Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (mg/m ³)	75 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
White Mineral Oil (Petroleum) (8042-47-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
USA ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³

8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing : No data available.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Consumer exposure controls : Avoid contact during pregnancy/while nursing.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquid.

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Color	: Colourless to yellow.
Odor	: Petroleum-like odour.
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 204 °C
Flash point	: > 94 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.88
Solubility	: Poorly soluble in water. Water: < 4 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 21.6 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Pour Point	: -36 °C
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content : < 2 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg body weight
2-(2-Butoxyethoxy) Ethanol (112-34-5)	
LD50 oral rat	5660 mg/kg (Rat)
LD50 dermal rabbit	2764 mg/kg (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
Dipropylene Glycol Monomethyl Ether (34590-94-8)	
LD50 oral rat	5135 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg; Rat; Experimental value)
LD50 dermal rat	9500 mg/kg (Rat; Literature study; Equivalent or similar to OECD 402; >19020 mg/kg bodyweight; Rat; Experimental value)

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dipropylene Glycol Monomethyl Ether (34590-94-8)	
LD50 dermal rabbit	9500 mg/kg (Rabbit; Literature study)
2,6-Di-tert-butylphenol (128-39-2)	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rat	> 1000 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit)
Dibutyl Phosphonate (1809-19-4)	
LD50 oral rat	3200 mg/kg (Rat)
LD50 dermal rabbit	1990 mg/kg (Rabbit)
Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Literature study; 5580 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight LD50 quoted as 14.1 mL/kg (12267 mg/kg using density of 0.87)
LC50 inhalation rat (mg/l)	> 28.1 mg/l/4h (Rat; Air, Literature study)
White Mineral Oil (Petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg (Rat; Experimental value,Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat; Experimental value)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
IARC group	3
Toluene (108-88-3)	
IARC group	3
White Mineral Oil (Petroleum) (8042-47-5)	
IARC group	3
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.
SECTION 12: Ecological information	
12.1. Toxicity	
2-(2-Butoxyethoxy) Ethanol (112-34-5)	
LC50 fish 1	1300 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Lepomis macrochirus; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	> 100 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Dipropylene Glycol Monomethyl Ether (34590-94-8)	
EC50 Daphnia 1	1919 mg/l (LC50; Equivalent or similar to OECD 202; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	969 mg/l (NOEC; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value)
Threshold limit algae 2	> 969 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Selenastrum capricornutum; Static system; Fresh water; Experimental value)
2,6-Di-tert-butylphenol (128-39-2)	
EC50 Daphnia 1	0.45 mg/l (EC50; 48 h)

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

White Mineral Oil (Petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	>= 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Weight of evidence)

Tri-para-cresylphosphate (78-32-0)	
LC50 fish 1	> 100 mg/l (LC50; 96 h)
EC50 other aquatic organisms 1	> 5 mg/l (28 h; Scenedesmus quadricauda; Photosynthesis)

12.2. Persistence and degradability

iLAST POWER STEERING FLUID 12 FL.OZ.	
Persistence and degradability	Not established.

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
Persistence and degradability	Not established.

2-(2-Butoxyethoxy) Ethanol (112-34-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.25 g O ₂ /g substance
Chemical oxygen demand (COD)	2.08 g O ₂ /g substance
ThOD	2.173 g O ₂ /g substance
BOD (% of ThOD)	0.11

Dipropylene Glycol Monomethyl Ether (34590-94-8)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available. Photolysis in the air.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
ThOD	2.06 g O ₂ /g substance
BOD (% of ThOD)	0

Petroleum Naphtha (64742-47-8)	
Persistence and degradability	Not established.

2,6-Di-tert-butylphenol (128-39-2)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water.
BOD (% of ThOD)	0.077 (5 days; Literature study)

Dibutyl Phosphonate (1809-19-4)	
Persistence and degradability	Biodegradability in water: no data available. Photodegradation in the air.

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	2.15 g O ₂ /g substance
Chemical oxygen demand (COD)	2.52 g O ₂ /g substance
ThOD	3.13 g O ₂ /g substance
BOD (% of ThOD)	0.69

White Mineral Oil (Petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil.

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)	
Persistence and degradability	Not established.

Paraffinum Liquidum (8012-95-1)	
Persistence and degradability	Not established.

Tri-para-cresylphosphate (78-32-0)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

iLAST POWER STEERING FLUID 12 FL.OZ.	
Bioaccumulative potential	Not established.

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
Bioaccumulative potential	Not established.

2-(2-Butoxyethoxy) Ethanol (112-34-5)	
BCF fish 1	0.46 (BCF)
Log Pow	0.56 (Experimental value)

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-(2-Butoxyethoxy) Ethanol (112-34-5)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Dipropylene Glycol Monomethyl Ether (34590-94-8)	
Log Pow	0.0043 (Experimental value; OECD 102: Melting Point/Melting Range; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Petroleum Naphtha (64742-47-8)	
Bioaccumulative potential	Not established.
2,6-Di-tert-butylphenol (128-39-2)	
BCF fish 1	660 (BCF; 72 h)
BCF other aquatic organisms 1	800 (BCF; 24 h)
Log Pow	4.92
Bioaccumulative potential	Not established.
Dibutyl Phosphonate (1809-19-4)	
Log Pow	1.81 (Estimated value)
Bioaccumulative potential	Bioaccumable.
Toluene (108-88-3)	
BCF fish 2	90 (BCF; 72 h; Leuciscus idus; Static system; Fresh water)
Log Pow	2.73 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
White Mineral Oil (Petroleum) (8042-47-5)	
Log Pow	> 6 (Calculated)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)	
Bioaccumulative potential	Not established.
Paraffinum Liquidum (8012-95-1)	
Bioaccumulative potential	Not established.
Tri-para-cresylphosphate (78-32-0)	
BCF fish 1	1589 (BCF; 168 h)
Log Pow	5.34
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).

12.4. Mobility in soil

2-(2-Butoxyethoxy) Ethanol (112-34-5)	
Surface tension	0.034 N/m (25 °C)
Toluene (108-88-3)	
Surface tension	0.03 N/m (20 °C)
Tri-para-cresylphosphate (78-32-0)	
Surface tension	0.044 N/m (25 °C)

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated,
ICAO/IATA (air): Not Regulated,
IMO/IMDG (water): Not Regulated,

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

iLAST POWER STEERING FLUID 12 FL.OZ.	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
2-(2-Butoxyethoxy) Ethanol (112-34-5)	
Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Reactive hazard
Petroleum Naphtha (64742-47-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard
Toluene (108-88-3)	
Subject to reporting requirements of United States SARA Section 313	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
White Mineral Oil (Petroleum) (8042-47-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

2-(2-Butoxyethoxy) Ethanol (112-34-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Petroleum Naphtha (64742-47-8)	
Toluene (108-88-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
White Mineral Oil (Petroleum) (8042-47-5)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

Petroleum Naphtha (64742-47-8)	
Toluene (108-88-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
White Mineral Oil (Petroleum) (8042-47-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

Petroleum Naphtha (64742-47-8)
Toluene (108-88-3)
White Mineral Oil (Petroleum) (8042-47-5)

15.3. US State regulations

iLAST POWER STEERING FLUID 12 FL.OZ.				
U.S. - California - Proposition 65 - Carcinogens List	No			
U.S. - California - Proposition 65 - Developmental Toxicity	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No			
State or local regulations	U.S. - California - Proposition 65			
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
2-(2-Butoxyethoxy) Ethanol (112-34-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Dipropylene Glycol Monomethyl Ether (34590-94-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Petroleum Naphtha (64742-47-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
2,6-Di-tert-butylphenol (128-39-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Dibutyl Phosphonate (1809-19-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	

iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

White Mineral Oil (Petroleum) (8042-47-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Lubricating Oils (Petroleum), C15-30, Hydrotreated Neutral Oil-Based (72623-86-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Paraffinum Liquidum (8012-95-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Tri-para-cresylphosphate (78-32-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

2-(2-Butoxyethoxy) Ethanol (112-34-5)				
State or local regulations				
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - New Jersey - Right to Know Hazardous Substance List				

Toluene (108-88-3)				
State or local regulations				
U.S. - California - Proposition 65 U.S. - New Jersey - Special Health Hazards Substances List New Jersey Right-to-Know U.S. - Massachusetts - Right To Know List Rhode Island Right to Know U.S. - Michigan - Critical Materials List U.S. - New Jersey - Environmental Hazardous Substances List U.S. - Illinois - Toxic Air Contaminants U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				


SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 1 - Must be preheated before ignition can occur.



iLAST POWER STEERING FLUID 12 FL.OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,
and are not reactive with water.

HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.