

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : iLAST ENGINE OIL STOP LEAK 12 FL.OZ.  
 Product code : FPIL0013

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine Stop Leak

#### 1.3. Details of the supplier of the safety data sheet

US Global Petroleum  
 9101 Fullerton Avenue  
 Franklin Park, IL 60131 - USA  
 T 773-376-9660

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Asp. Tox. 1 H304

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
 Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways  
 Precautionary statements (GHS-US) : P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
 P331 - Do NOT induce vomiting  
 P405 - Store locked up  
 P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

| Name   | Product identifier  | %     | GHS-US classification |
|--|---------------------|-------|-----------------------|
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic | (CAS No) 64742-52-5 | >= 95 | Asp. Tox. 1, H304     |
| Diisodecyl Adipate                                     | (CAS No) 27178-16-1 | 1 - 5 | Not classified        |

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
 First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.  
 First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

# iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms.
- Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
- Symptoms/injuries after eye contact : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Always wash hands after handling the product. Remove contaminated clothes. Wash affected areas thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

# iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.3. Specific end use(s)

Follow Label Directions.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) |                                     |                                  |
|---|-------------------------------------|----------------------------------|
| USA ACGIH   | ACGIH TWA (mg/m <sup>3</sup> )      | 5 mg/m <sup>3</sup> MIST 8 HOURS |
| USA OSHA  | OSHA PEL (TWA) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup> MIST 8 HOURS |

### 8.2. Exposure controls

Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.  
Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



Hand protection : Wear protective gloves.  
Eye protection : Chemical goggles or safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Wear respiratory protection.  
Consumer exposure controls : Avoid contact during pregnancy/while nursing.  
Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Liquid.  
Color : Red.  
Odor : Petroleum-like odour.  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : 0 °C  
Freezing point : No data available  
Boiling point : > 100 °C  
Flash point : 174 °C  
Auto-ignition temperature : 315 °C  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : < 0.011 kPa  
Relative vapor density at 20 °C : No data available  
Relative density : 0.9  
Solubility : Insoluble in water.  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : 19.5 cSt @ 40 deg C  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : No data available

### 9.2. Other information

VOC content : < 1 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

# iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) |                          |
|---|--------------------------|
| LD50 oral rat   | > 5000 mg/kg body weight |
| Diisodecyl Adipate (27178-16-1)                                     |                          |
| LD50 oral rat   | 20500 mg/kg (Rat)        |
| LD50 dermal rat   | > 5000 mg/kg (Rat)       |

Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified Based on available data, the classification criteria are not met  
Carcinogenicity : Not classified

| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) |   |
|---|---|
| IARC group  | 3 |

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : Not classified  
Aspiration hazard : May be fatal if swallowed and enters airways.  
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.  
Symptoms/injuries after inhalation : May cause irritation or asthma-like symptoms.  
Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.  
Symptoms/injuries after eye contact : May cause slight eye irritation . Inflammation/damage of the eye tissue. Irritation of the eye tissue. Redness of the eye tissue.  
Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways. May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

| iLAST ENGINE OIL STOP LEAK 12 FL.OZ.                                |   |
|---|---|
| Persistence and degradability                                       | Not established.                              |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) |   |
| Persistence and degradability                                       | Not established.                              |
| Diisodecyl Adipate (27178-16-1)                                     |   |
| Persistence and degradability                                       | Biodegradability in water: no data available. |

### 12.3. Bioaccumulative potential

| iLAST ENGINE OIL STOP LEAK 12 FL.OZ.                                |                  |
|---|------------------|
| Bioaccumulative potential   | Not established. |
| Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5) |                  |
| Bioaccumulative potential   | Not established. |

# iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Diisodecyl Adipate (27178-16-1)

|                           |                                    |
|---------------------------|------------------------------------|
| Bioaccumulative potential | No bioaccumulation data available. |
|---------------------------|------------------------------------|

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground): Not regulated,

ICAO/IATA (air): Not Regulated,

IMO/IMDG (water): Not Regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

|                                     |                                 |
|-------------------------------------|---------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard |
|-------------------------------------|---------------------------------|

#### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

|                                     |                                 |
|-------------------------------------|---------------------------------|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard |
|-------------------------------------|---------------------------------|

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

# iLAST ENGINE OIL STOP LEAK 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

| iLAST ENGINE OIL STOP LEAK 12 FL.OZ.                                |    |
|---|----|
| U.S. - California - Proposition 65 - Carcinogens List               | No |
| U.S. - California - Proposition 65 - Developmental Toxicity         | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | No |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Male   | No |

### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| No  | No  | No  | No  |                                   |

### Diisodecyl Adipate (27178-16-1)

| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | Non-significant risk level (NSRL) |
|---|---|---|---|-----------------------------------|
| No  | No  | No  | No  |                                   |

## SECTION 16: Other information

Indication of changes : Revision - See : \*


Other information : None.

Full text of H-phrases:

H304

May be fatal if swallowed and enters airways

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 1 - Must be preheated before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible  
Flammability : 1 Slight Hazard  
Physical : 0 Minimal Hazard  
Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*