



**PREMIUM TRACTOR HYDRAULIC FLUID**

**USGLOBAL 303 Tractor Hydraulic Fluid**

USGLOBAL 303 Tractor Hydraulic Fluid is an economic, low viscosity, single grade lubricant formulated from a blend of highly refined base oils with a high-performance additive package. It provides excellent results in rust protection, water sensitivity, extreme pressure/anti-wear properties and foam suppression. It is suitable for lubricate in older tractor transmission, differential and final drive gears in tractors and implements where a economic fluid is desired. It is also recommended as a replacement fluid for Allis Chalmers, Allison, Ford Tractor, Caterpillar, International Harvester, Deutz, Oliver, White, J.I. Case, Massey Ferguson, John Deere and other manufacturers where a tractor hydraulic fluid is recommended. 303 Tractor Hydraulic Fluid is recommended for model years earlier than 1974. For equipment built after 1974 USGLOBAL Premium Universal Tractor Hydraulic Fluid J20-C is recommended.

**USGLOBAL Tractor Hydraulic Fluid J20-C**

USGLOBAL Tractor Hydraulic Fluid J20-C is a premium quality multi-functional tractor hydraulic fluid blended from highly refined base oils and an additive package suitable for use in equipment requiring extended service under severe conditions. It provides excellent oxidation, anti-foam, anti-rust, anti-wear, extreme pressure (EP) protection. It is recommended for final drive, transmission, differential power take-off (PTO) units and wet brake systems. USGLOBAL Premium J20-C Tractor Hydraulic Fluid has been field-tested and is suitable for use in Allis Chalmers, Allison, Ford Tractor, Caterpillar, International Harvester, Kubota, Deutz, Oliver, White, J.I. Case, Massey Ferguson, John Deere and other manufacturers' equipment where a premium J20-C tractor hydraulic fluid is recommended.

**Typical Characteristics - Tractor Hydraulic Fluid - V140213**

GRADE		303	J20-C
SAE Grade		20	30
Color	ASTM 1500	6 max	4 max
Viscosity @ 100°C, cSt	ASTM 445	7.9	9.2
Viscosity @ 40°C, cSt	ASTM 445	40-68	53
Viscosity Index	ASTM 2270	61 min.	135
Flash Point, COC °C/°F	ASTM 92	204 / 400	204/400
Pour Point °C/°F	ASTM 97	-17 / 0	-29 / -20
API Gravity	ASTM 1298	30	29

Typical ASTM test data are average values only. Minor variations, which do not affect performance, may occur.



HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (MSDS) Material Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.