

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Trade name : iLAST OCTANE BOOSTER 12 FL.OZ.  
 Product code : FPI0010

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Octane Enhancer

#### 1.3. Details of the supplier of the safety data sheet

US Global Petroleum  
 9101 Fullerton Avenue  
 Franklin Park, IL 60131 - USA  
 T 773-376-9660

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 4 H227  
 Asp. Tox. 1 H304

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger  
 Hazard statements (GHS-US) : H227 - Combustible liquid  
 H304 - May be fatal if swallowed and enters airways  
 Precautionary statements (GHS-US) : P210 - Keep away from all ignition sources. - No smoking  
 P280 - Wear protective gloves, protective clothing, eye protection, face protection  
 P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,  
 P331 - Do NOT induce vomiting  
 P370+P378 - In case of fire: See Section 5.1 Extinguishing Media  
 P403+P235 - Store in a well-ventilated place. Keep cool  
 P405 - Store locked up  
 P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	>= 95	Asp. Tox. 1, H304
2-Methoxy-2-Methylpropane	(CAS No) 1634-04-4	1 - 5	Flam. Liq. 2, H225 Skin Irrit. 2, H315

The exact percentage is a trade secret.

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Respiratory arrest: artificial respiration or oxygen. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove the victim into fresh air. If you feel unwell, seek medical advice. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash contaminated clothing before reuse. If skin irritation occurs: seek medical attention. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Get medical advice/attention. Immediately flush eyes thoroughly with water for at least 15 minutes. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: May cause slight eye irritation . May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid.
Explosion hazard	: May form flammable/explosive vapor-air mixture.
Reactivity	: On heating: release of harmful/irritant gases/vapours.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate ignition sources. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Use protective clothing. Ventilate area. Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Absorbed substance: shovel into drums. Cover spill with inert material, e.g.: sand, earth, vermiculite or kieselguhr, powdered limestone. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking.
- Handling temperature : Do not heat or store at temperature above 120 F
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash affected areas thoroughly after handling. Always wash hands after handling the product. Remove contaminated clothes. Separate working clothes from town clothes. Launder separately.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Comply with applicable regulations. Provide local exhaust or general room ventilation. Take precautionary measures against static discharge.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place.
- Incompatible products : Oxidizing agent. Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 2-Methoxy-2-Methylpropane (1634-04-4)

USA ACGIH	ACGIH TWA (ppm)	50 ppm (Methyl-tert butyl ether (MTBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
-----------	-----------------	---

##### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours
-----------	-----------------	-----------------

#### 8.2. Exposure controls

- Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Ensure good ventilation of the work station. Local exhaust ventilation, vent hoods.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
- Hand protection : Wear protective gloves.
- Eye protection : Face shield. Chemical goggles or safety glasses.
- Skin and body protection : Protective clothing.
- Respiratory protection : Wear gas mask if concentration in air > exposure limit. Respiratory protection of the dependent type. Wear respiratory protection.
- Environmental exposure controls : Avoid release to the environment.
- Consumer exposure controls : Avoid contact during pregnancy/while nursing.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colourless to light yellow.
- Odor : Ethereal. Strong odour.
- Odor threshold : No data available
- pH : N/A
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point	: No data available
Boiling point	: > 240 °C
Flash point	: 55 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: N/A
Relative vapor density at 20 °C	: No data available
Relative density	: 0.798
Solubility	: Poorly soluble in water. Water: < 2 % Slight
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 1.7 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 0.7 - 6 vol % Estimated

### 9.2. Other information

VOC content : 2.5 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

On heating: release of harmful/irritant gases/vapours.

### 10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7). Combustible liquid. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

May react violently with oxidants. Not established.

### 10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

iLAST OCTANE BOOSTER 12 FL.OZ.	
LC50 inhalation rat (ppm)	23576 ppm/4h Methyl tert-butyl ether (MTBE)
2-Methoxy-2-Methylpropane (1634-04-4)	
LD50 oral rat	4000 mg/kg (Rat)
LD50 dermal rat	> 6800 mg/kg (Rat)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit)
LC50 inhalation rat (mg/l)	85 mg/l/4h (Rat)
LC50 inhalation rat (ppm)	23576 ppm/4h (Rat)
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects

Skin corrosion/irritation : Not classified  
pH: N/A

Serious eye damage/irritation : Not classified  
pH: N/A

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### 2-Methoxy-2-Methylpropane (1634-04-4)

IARC group	3
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause moderate irritation. Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: May cause slight eye irritation . May cause severe irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### 2-Methoxy-2-Methylpropane (1634-04-4)

LC50 fish 1	672 - 706 mg/l (LC50; 96 h; Pimephales promelas)
EC50 Daphnia 1	651 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna)

### 12.2. Persistence and degradability

#### iLAST OCTANE BOOSTER 12 FL.OZ.

Persistence and degradability	Not established.
-------------------------------	------------------

#### 2-Methoxy-2-Methylpropane (1634-04-4)

Persistence and degradability	Not readily biodegradable in water.
-------------------------------	-------------------------------------

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### iLAST OCTANE BOOSTER 12 FL.OZ.

Bioaccumulative potential	Not established.
---------------------------	------------------

#### 2-Methoxy-2-Methylpropane (1634-04-4)

BCF fish 1	1.5 (BCF; 672 h)
Log Pow	1.06 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### Distillates (Petroleum), Hydrotreated Light (64742-47-8)

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

#### 2-Methoxy-2-Methylpropane (1634-04-4)

Surface tension	0.020 N/m (20 °C)
-----------------	-------------------

### 12.5. Other adverse effects

Other information	: Avoid release to the environment.
-------------------	-------------------------------------

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, MTBE), 3, III, Limited Quantity
ICAO/IATA (air):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, MTBE), 3, III, Limited Quantity
IMO/IMDG (water):	UN1993, Flammable liquids, n.o.s. (Petroleum Distillates, MTBE)(55 deg C c.c.), 3, III, Limited Quantity
Special Provisions:	<p>B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable</p> <p>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks</p> <p>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)</p> <p>T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)</p> <p>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = <math>97 / 1 + a (tr - tf)</math> Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling</p> <p>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP</p>

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (Petroleum Distillates, MTBE)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Special Provisions (49 CFR 172.102)	<p>: B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable</p> <p>B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks</p> <p>IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672)</p> <p>T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)</p> <p>TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = <math>97 / 1 + a (tr - tf)</math> Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling</p> <p>TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP</p>
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

#### 14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

#### Overland transport

No additional information available

#### Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
-----------------------------	--

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L  
CFR 175.75)

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

iLAST OCTANE BOOSTER 12 FL.OZ.	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard
2-Methoxy-2-Methylpropane (1634-04-4)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

### 15.2. International regulations

#### CANADA

iLAST OCTANE BOOSTER 12 FL.OZ.	
WHMIS Classification	Class B Division 2 - Flammable Liquid
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

R10

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

iLAST OCTANE BOOSTER 12 FL.OZ.				
U.S. - California - Proposition 65 - Carcinogens List	No			
U.S. - California - Proposition 65 - Developmental Toxicity	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No			
2-Methoxy-2-Methylpropane (1634-04-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Distillates (Petroleum), Hydrotreated Light (64742-47-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

# iLAST OCTANE BOOSTER 12 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

Other information : None.


Full text of H-phrases:

H225	Highly flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*