

Technical Product Information

773-376-9660
usglobalpetroleum.com



API SN PLUS

Synthetic Blend SAE 10W-40 Motor Oil

Tiger's Head Synthetic Blend SAE 10W-40 Motor Oil a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Tiger's Head Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Tiger's Head Synthetic Blend SAE 10W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SN PLUS service classification and is compatible with all prior API categories. Tiger's Head Synthetic Blend SAE 10W-40 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A3/B3/B4, MB 229.3, RN 0710/0700, VW 502 00 / 505 00, and many other OEM's specifications where a synthetic blend API SN motor oil is recommended.

Benefits and Applications

- Tiger's Head Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 10W-40 Synthetic Blend Oil

| SAE GRADE | Syn Blend | 10W-40 |
|------------------------|------------|-------------|
| API SERVICE | | SN PLUS |
| API Gravity | ASTM D287 | 32.55 |
| Flash Point, COC °C/°F | ASTM D92 | 243 / 469.4 |
| Pour Point, °C/°F | ASTM D97 | -41 / -41.8 |
| Viscosity @ 40°C, cSt | ASTM D445 | 110.55 |
| Viscosity @ 100°C, cSt | ASTM D445 | 16.06 |
| Viscosity Index | ASTM D2270 | 156 |
| CCS, mPa-sec °C max | ASTM D5293 | 7000 @ -25 |
| Total Base No. TBN | ASTM D2896 | 7.6 |

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SN PLUS

ACEA A3/B3/B4, MB 229.3,
RN 0710/0700,
VW 502 00 / 505 00



V200308

HANDLING AND SAFETY INFORMATION - Refer to ROVER (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660 - www.usglobalpetroleum.com