Technical Product Information www.usglobalpetroleum.com www.everestoil.com

SP / GF-6A

773-376-9660

Premium Performance

EVERES

Synthetic Blend SAE OW-20 Motor Oil

Everest Synthetic Blend SAE 0W-20 Motor Oil a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Everest Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Everest Synthetic Blend SAE 0W-20 Motor Oil meets or exceeds GF-6A and Resource Conserving SP service classifications and is compatible with all prior categories. Everest Synthetic Blend SAE 0W-20 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including GM 6094M, Chrysler MS6395, Ford WSS-M2C947A and many other OEM's specifications where a synthetic blend SP motor oil is recommended.

Benefits and Applications

- Everest Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 0W-20 Synthetic Blend Oil

SAE GRADE	Syn Blend	0W-20
API SERVICE		SP/GF-6A
API Gravity	ASTM D287	33.47
Flash Point, COC °C/°F	ASTM D92	219 / 426.2
Pour Point, °C/°F	ASTM D97	-45 / -49
Viscosity @ 40°C, cSt	ASTM D445	46.76
Viscosity @ 100°C, cSt	ASTM D445	8.76
Viscosity Index	ASTM D2270	169
CCS, mPa-sec °C max	ASTM D5293	6200 @ -35
Total Base No. TBN	ASTM D2896	7.4

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

SP / ILSAC GF-6A

Ford WSS-M2C945A, GM 6094M, Chrysler MS6395



V210607

HANDLING AND SAFETY INFORMATION - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.