



# GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

## Full Synthetic SAE 5W-30 Motor Oil

**Golden Stallion dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil** is formulated from select low-friction, full synthetic base stocks and an advanced technology additive system licensed by General Motors to meet their Global Engine Oil Specification. It provides excellent oxidation stability, superior resistance to sludge formation and varnish deposits, reduces friction and wear at start-up and protects your engine even under the toughest driving conditions. Golden Stallion dexos1™ GEN 2 Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile and stationary engines.

**Golden Stallion dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil** meets or exceeds stringent GM dexos1™ GEN 2 requirements, ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classifications as well as all earlier API categories. Golden Stallion dexos1™ GEN 2 Full Synthetic SAE 5W-30 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including Chrysler MS6395M, Ford WSS-M2C929A, WSS-M2C946A, GM 6094M, Porsche, Renault, and other OEM's specifications where a full synthetic API SP motor oil is recommended.

### Benefits and Applications

- Maximum full synthetic dexos1<sup>®</sup> GEN 2 protection
- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Superior resistance to sludge and varnish deposit formation

### 5W-30 Typical Characteristics - V210802

SAE GRADE	dexos1™	5W-30
API SERVICE		SP/GF-6A
API Gravity	ASTM D287	35.62
Flash Point, COC °C/°F	ASTM D92	228 / 442.4
Pour Point, °C/°F	ASTM D97	-48 / -54.4
Viscosity @ 40°C, cSt	ASTM D445	61.12
Viscosity @ 100°C, cSt	ASTM D445	10.94
Viscosity Index	ASTM D2270	173
CCS, mPa-sec °C max	ASTM D5293	3730 @ -30
Total Base No. TBN	ASTM D2896	8.0

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

### API SP ILSAC GF-6A

GM 6094M, Chrysler  
MS6395M, Ford WSS-  
M2C929A, WSS-M2C946A,  
Porsche, Renault



**HANDLING AND SAFETY INFORMATION** - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.