



GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

Synthetic Blend High Mileage SAE 5W-20 Motor Oil

Golden Stallion Synthetic Blend High Mileage SAE 5W-20 Motor Oil is formulated with a low friction additive package designed especially for engines with over 75,000 miles. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against sludge and varnish deposits and provides additional anti-wear protection that helps extend engine life. Golden Stallion High Mileage Motor Oil is recommended for passenger car, truck, sport utility vehicle and other engines with over 75,000 miles.

Golden Stallion Synthetic Blend High Mileage SAE 5W-20 Motor Oil meets or exceeds ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classifications and is compatible with all prior API categories. It has been field tested to be comparable to most American, Asian and European manufacturers' standards including Ford WSS-M2C945A, GM 6094M, Chrysler MS6395 and many other OEM's specifications where a synthetic blend API SP motor oil is recommended.

Benefits and Applications

- Golden Stallion Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 5W-20 Synthetic Blend Oil

SAE GRADE	Syn Blend	5W-20
API SERVICE		SP/GF-6A
API Gravity	ASTM D287	33.48
Flash Point, COC °C/°F	ASTM D92	219 / 426.2
Pour Point, °C/°F	ASTM D97	-49 / -56.2
Viscosity @ 40°C, cSt	ASTM D445	50.15
Viscosity @ 100°C, cSt	ASTM D445	8.7
Viscosity Index	ASTM D2270	152
CCS, mPa-sec °C max	ASTM D5293	6600 @ -30
Total Base No. TBN	ASTM D2896	7.1

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SP ILSAC GF-6A

Ford WSS-M2C945A, GM
6094M, Chrysler MS6395



V211209

HANDLING AND SAFETY INFORMATION - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.