



# GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

## Synthetic Blend SAE 5W-40 Motor Oil

**Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil** is a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Golden Stallion Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

**Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil** meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including GM 6094M, Chrysler MS6395M and many other OEM's specifications where a synthetic API SP motor oil is recommended.

### Benefits and Applications

- Golden Stallion Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

### Typical Characteristic 5W-40 Synthetic Blend Oil

SAE GRADE	Syn Blend	5W-40
API SERVICE		SP
API Gravity	ASTM D287	35.0
Flash Point, COC °C/°F	ASTM D92	205 / 401
Pour Point, °C/°F	ASTM D97	-38 / -36.4
Viscosity @ 40°C, cSt	ASTM D445	84.0
Viscosity @ 100°C, cSt	ASTM D445	15
Viscosity Index	ASTM D2270	145
CCS, mPa-sec °C max	ASTM D5293	6200 @ -30
Total Base No. TBN	ASTM D2896	7.9

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

### API SP

GM 6094M, Chrysler  
MS6395M



V210802

HANDLING AND SAFETY INFORMATION - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.