



GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

4T 25W-60 Motorcycle Engine Oil

Golden Stallion 4T SAE 25W-60 Synthetic Blend Motorcycle Engine is designed specifically for high-temperature, high RPM, 4-stroke engines used in on and off-road motorcycles, ATVs and similar vehicles. It is a premium quality multi-grade engine oil designed with high-tech, low friction performance additives that deliver advanced low temperature fluidity to ensure easy cranking and startup protection. It provides outstanding anti-wear protection, exceptional control and resistance of performance robbing sludge and varnish deposits and provides superior frictional characteristics for maximum power transfer, smooth shifting and superb wet clutch protection even under the most severe riding conditions.

Golden Stallion 4T SAE 25W-60 Synthetic Blend Motorcycle Engine meets or exceeds API SL service classification and is compatible with all prior API classifications. Golden Stallion Synthetic Blend 4T SAE 25W-60 Motorcycle Engine Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including JASO MA/MA2 many other OEM's specifications where a synthetic blend API SL motorcycle engine oil is recommended.

Benefits and Applications

- For use in on / off-road 4-stroke motorcycles and ATVs
- Resists breakdown in the most severe engine environments
- Optimum protection over a wide operating temperature
- Excellent wear, corrosion, and rust protection
- Superior wet clutch protection

Typical Characteristic 25W-60 Synthetic Blend Oil V211208

SAE GRADE	Syn Blend	25W-60
API SERVICE		SL
API Gravity	ASTM D287	27
Flash Point, COC °C/°F	ASTM D92	250 / 428
Pour Point, °C/°F	ASTM D97	-18 / -0.4
Viscosity @ 40°C, cSt	ASTM D445	244
Viscosity @ 100°C, cSt	ASTM D445	24
Viscosity Index	ASTM D2270	120
CCS, mPa-sec °C max	ASTM D5293	13000 @ -10
Total Base No. TBN	ASTM D2896	-

**API SL
JASO MA2**



Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.