



GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

Synthetic Blend SAE 5W-40 Motor Oil

Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil is a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Golden Stallion Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. Golden Stallion Synthetic Blend SAE 5W-40 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A3/B4 & A5/B5, GM 6094M, Chrysler MS6395M and many other OEM's specifications where a synthetic API SP motor oil is recommended.

Benefits and Applications

- Golden Stallion Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 5W-40 Synthetic Blend Oil

| SAE GRADE | Syn Blend | 5W-40 |
|------------------------|------------|-------------|
| API SERVICE | | SP |
| API Gravity | ASTM D287 | 35.0 |
| Flash Point, COC °C/°F | ASTM D92 | 205 / 401 |
| Pour Point, °C/°F | ASTM D97 | -38 / -36.4 |
| Viscosity @ 40°C, cSt | ASTM D445 | 84.0 |
| Viscosity @ 100°C, cSt | ASTM D445 | 15 |
| Viscosity Index | ASTM D2270 | 145 |
| CCS, mPa-sec °C max | ASTM D5293 | 6200 @ -30 |
| Total Base No. TBN | ASTM D2896 | 7.9 |

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SP

ACEA A3/B4 & A5/B5,
GM 6094M, Chrysler
MS6395M



V200722

HANDLING AND SAFETY INFORMATION - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.