

# Technical Product Information

www.usglobalpetroleum.com

www.everestoil.com

773-376-9660



dexos1™ GEN 2 License # D130BBBC299

**Premium  
Performance**

**API SP  
ILSAC GF-6A**

# EVEREST®

## Full Synthetic SAE 0W-20 Motor Oil

**EVEREST dexos1™ GEN 2 Full Synthetic SAE 0W-20 Motor Oil** is formulated from select low-friction, full synthetic base stocks and an advanced technology additive system licensed by General Motors to meet their Global Engine Oil Specification. It provides excellent oxidation stability, superior resistance to sludge formation and varnish deposits, reduces friction and wear at start-up. EVEREST dexos1™ GEN 2 Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile and stationary engines.

**EVEREST dexos1™ GEN 2 Full Synthetic SAE 0W-20 Motor Oil** meets or exceeds stringent GM dexos1™ GEN 2 requirements, ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classification as well as all earlier API categories. EVEREST dexos1™ GEN 2 Full Synthetic SAE 0W-20 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including ACEA A1/B1 & A5/B5, GM 6094M, Chrysler MS6395, Ford WSS-M2C947A, and many other OEM's specifications where a full synthetic API SP motor oil is recommended.

### Benefits and Applications

- Maximum full synthetic dexos1® GEN 2 protection
- Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Superior resistance to sludge and varnish deposit formation

### 0W-20 Typical Characteristics - V200601

| SAE GRADE              | dexos1™    | 0W-20       |
|------------------------|------------|-------------|
| API SERVICE            |            | SP/GF-6A    |
| API Gravity            | ASTM D287  | 35.88       |
| Flash Point, COC °C/°F | ASTM D92   | 235 / 455   |
| Pour Point, °C/°F      | ASTM D97   | -51 / -59.8 |
| Viscosity @ 40°C, cSt  | ASTM D445  | 42.76       |
| Viscosity @ 100°C, cSt | ASTM D445  | 8.106       |
| Viscosity Index        | ASTM D2270 | 166         |
| CCS, mPa·sec °C max    | ASTM D5293 | 6200 @ -35  |
| Total Base No. TBN     | ASTM D2896 | 8.1         |

Typical test data are average values only.  
Minor variations, which do not affect performance, may occur.

**API SP  
ILSAC GF-6A**

ACEA A1/B1 & A5/B5, GM  
6094M, Chrysler MS6395,  
Ford WSS-M2C947A



**HANDLING AND SAFETY INFORMATION** - Refer to EVEREST (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.