

CNG MultiFuel SAE 20W-50 Engine Oil

Petromerica CNG MultiFuel SAE 20W-50 Engine Oil is a premium multifuel oil specifically designed for engines using Compressed Natural Gas (CNG), LPG, Dual Fuel, naturally aspirated diesel, or gasoline. It provides superior high-temperature protection, reduces friction and protects your engine against performance robbing wear, sludge and varnish deposits. It is suitable for bus, taxi, passenger car, truck, and other light-duty vehicles. Petromerica CNG Multi SAE 20W-50 Engine Oil meets or exceeds American Petroleum Institute (API) SN service classification and has been field tested to be comparable to American, Asian and European manufacturers' standards including JASO MA/MA2, GM6094M, Volvo VDS, MB 228.1 & 229.1, MAN 271, and Mack EO/L as well as the ash and TBN requirements of major OEMs.

Benefits and Applications

- For gas fueled (natural gas and LPG) engines
- Advanced high temperature and sludge protection
- Exceeds API SN, SM, SL service classification

CNG 20W-50 Typical Characteristics - V210927

SAE GRADE	Syn Blend	20W-50
SERVICE CLASSIFICATION		SN
API Gravity	ASTM D287	29.7
Flash Point, COC °C/°F	ASTM D92	206 / 402.8
Pour Point, °C/°F	ASTM D97	-30 / -22
Viscosity @ 40°C, cSt	ASTM D445	156.9
Viscosity @ 100°C, cSt	ASTM D445	18.6
Viscosity Index	ASTM D2270	133
CCS, mPa-sec °C max	ASTM D5293	9500 @ -15
Total Base No. TBN	ASTM D2896	7.9

Typical test data are average values only.

Minor variations, which do not affect performance, may occur.

Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

www.usglobalpetroleum.com www.petromericaoil.com

SN Service

JASO MA/MA2, GM6094M, Volvo VDS, MB 228.1 & 229.1, MAN 271, and Mack EO/L

