

Semi Synthetic High Mileage 10W-40 Motor Oil

Petromerica Semi Synthetic High Mileage SAE 10W-40 Motor Oil is formulated with a low friction additive package designed especially for engines with over 75,000 miles. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against sludge and varnish deposits and provides additional anti-wear protection that helps extend engine life. It is recommended for passenger car, truck, sport utility vehicle and other engines with over 75,000 miles.

Petromerica Semi Synthetic High Mileage SAE 10W-40 Motor Oil meets or exceeds American Petroleum Institute (API) SP service classification and is compatible with all prior API categories. Petromerica Semi Synthetic High Mileage SAE 10W-40 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including MB 229.3, RN 0710/0700, VW 502.00 / 505.00, and many other OEM's specifications where a semi synthetic API SP motor oil is recommended.

Benefits and Applications

- For vehicles with over 75.000 miles
- · Lower pour point reduces start-up wear during cold weather
- Enhanced oxidative stability, emission system and wear protection
- Semi synthetic oil helps to improve fuel economy

10W-40 Typical Characteristics - V210603

SAE GRADE		10W-40
SERVICE CLASSIFICATION		SP
API Gravity	ASTM D287	32.55
Flash Point, COC °C/°F	ASTM D92	243 / 469.4
Pour Point, °C/°F	ASTM D97	-41 / -41.8
Viscosity @ 40°C, cSt	ASTM D445	108.1
Viscosity @ 100°C, cSt	ASTM D445	15.87
Viscosity Index	ASTM D2270	157
CCS, mPa-sec °C max	ASTM D5293	7000 @ -25
Total Base No. TBN	ASTM D2896	7.5

Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API SP

MB 229.3, RN 0710/0700, VW 502.00 / 505.00







Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information, data or products can be used without infringing patents of third parties.