

SAE-40 MARINE MOTOR OIL

Petromerica Marine Motor Oil is a premium quality monograde motor oil formulated with a special additive package designed especially for modern engines used in boating applications. It provides excellent protection against wear rust, and corrosion and helps minimize performance robbing carbon, sludge and varnish deposits. Petromerica Marine Motor Oil is recommended for gasoline and diesel engines including high-output, medium-speed engines using high sulfur gas or marine diesel fuel.

Petromerica SAE-40 Marine Motor Oil meets or exceeds the performance requirements of all diesel (both two- and four-cycle) and gasoline engine manufacturers specifying the use of a SAE-40 engine oil meeting API CF-2, CF/SL, CD, SH, SJ Service Classifications. It has been field tested to be comparable to a host of diesel and gasoline engine manufactured standards including Caterpillar, Cummins, Detroit Diesel, International/Navistar, John Deere, Mercedes Benz, MTU, Yanmar, Perkins, Volvo, Chrysler, Ford, Mercury, Indmar and where an API CF-2 marine motor oil is recommended.

Benefits and Applications

- Helps reduce oil consumption
- Outstanding piston cleanliness
- Exceptionally anti-wear properties
- Helps protect against ring and cylinder wear
- Recommended for gasoline and diesel engines

Typical Characteristic SAF-40 Marine Oil

SAE GRADE		SAE-40
API SERVICE		CF-2, CF
API Gravity	ASTM D287	25.97
Flash Point, COC °C/°F	ASTM D92	249 / 480
Pour Point, °C/°F	ASTM D97	-19 / -2.2
Viscosity @ 40°C, cSt	ASTM D445	147
Viscosity @ 100°C, cSt	ASTM D445	14.97
Viscosity Index	ASTM D2270	101
CCS, mPa-sec °C max	ASTM D5293	-
Total Base No. TBN	ASTM D2896	30

Typical test data are average values only.

Minor variations, which do not affect performance, may occur.

API CF-2, CF





Manufactured by US Global Petroleum, Franklin Park, IL 60131 - 773-376-9660

HANDLING AND SAFETY INFORMATION - Refer to USGLOBAL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information, data or products can be used without infringing patents of third parties.