

ROVER™

FULL SYNTHETIC MOTOR OIL

Rover Full Synthetic SAE 5W-30 Motor Oil is a superior quality multi-grade motor oil designed with a state-of-the-art low friction additive system for maximum engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. Rover Full Synthetic Motor Oil is recommended for turbo-charged and high-powered passenger car, truck, sport utility vehicle and other mobile or stationary engines.

Rover Full Synthetic SAE 5W-30 Motor Oil meets or exceeds ILSAC GF-6A and American Petroleum Institute (API) Resource Conserving SP service classifications and is compatible with all prior API categories. Rover Full Synthetic SAE 5W-30 motor oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including GM 6094M, Chrysler MS6395M, Ford WSS-M2C929A, WSS-M2C946A, Porsche, Renault, and other OEM's specifications where a full synthetic API SP motor oil is recommended.

Benefits and Applications

- Exceeds API SP / ILSAC GF-6A service
- Helps optimize fuel economy
- Compatible with and outperforms conventional motor oil
- Maximum engine cleanliness and protection

5W-30 Typical Characteristics - V210628

| SAE GRADE | Full Syn | 5W-30 |
|------------------------|------------|-------------|
| API SERVICE | | SP/GF-6A |
| API Gravity | ASTM D287 | 35.58 |
| Flash Point, COC °C/°F | ASTM D92 | 227 / 440.6 |
| Pour Point, °C/°F | ASTM D97 | -46 / -50.8 |
| Viscosity @ 40°C, cSt | ASTM D445 | 61.68 |
| Viscosity @ 100°C, cSt | ASTM D445 | 10.68 |
| Viscosity Index | ASTM D2270 | 165 |
| CCS, mPa-sec °C max | ASTM D5293 | 6600 @ -30 |
| Total Base No. TBN | ASTM D2896 | 8.2 |

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to ROVER (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

API SP ILSAC GF-6A

GM 6094M, Chrysler
MS6395M, Ford
WSS-M2C929A,
WSS-M2C946A,
Porsche, Renault

