

ROVER™

Full Synthetic SAE 0W-20 Motor Oil

ROVER dexos1™ GEN 3 Full Synthetic SAE 0W-20 Motor Oil blends the latest 7th generation additives with an advanced additive system licensed by General Motors to meet their Global GEN3 Engine Oil Specification. It delivers remarkable improvements in performance, wear protection, oxidation control, pre-ignition prevention, and fuel economy, as well as superior resistance to sludge formation and varnish deposits for today's automobiles, light trucks, SUVs, and other engines, including the latest advanced hybrid and turbocharged gasoline engines.

ROVER dexos1™ GEN 3 Full Synthetic SAE 0W-20 Motor Oil meets rigorous GM dexos1™ GEN 3 requirements and surpasses ILSAC GF-7A and American Petroleum Institute (API) Resource Conserving SQ classifications. It is compatible with all prior API categories and has been field-tested to be comparable to most equivalent American, Asian, and European manufacturers' standards, including but not limited to Chrysler MS 6395, Ford WSS-M2C947A, GM 6094M, and other OEM's specifications where a full synthetic SAE 0W-20 API SQ motor oil is recommended.

Benefits and Applications

- Exceeds Next-level API SQ / ILSAC GF-7A Technology
- Maximum full synthetic dexos1® GEN 3 protection
- Better fuel economy and extended engine life
- Enhanced oxidative stability, emission system, and wear protection



Typical Characteristics Full Synthetic 0W-20

| SAE GRADE | dexos1™ | 0W-20 |
|------------------------|------------|-------------|
| API SERVICE | | SQ/GF-7A |
| API Gravity | ASTM D287 | 35.88 |
| Flash Point, COC °C/°F | ASTM D92 | 235 / 455 |
| Pour Point, °C/°F | ASTM D97 | -51 / -59.8 |
| Viscosity @ 40°C, cSt | ASTM D445 | 42.76 |
| Viscosity @ 100°C, cSt | ASTM D445 | 8.106 |
| Viscosity Index | ASTM D2270 | 166 |
| CCS, mPa-sec °C max | ASTM D5293 | 6200 @ -35 |
| Total Base No. TBN | ASTM D2896 | 8.1 |

API SQ ILSAC GF-7A

GM dexos 1™ GEN 3
Chrysler MS 6395
Ford WSS-M2C947A
GM 6094M



V260320



Test Method ASTM - Typical test data are average values only.
Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to ROVER (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.