

# iLAST™ EXTENDED LIFE

## EURO PINK 50/50 Antifreeze/Coolant

**For use in Audi, Volkswagen, Porsche, and other automotive and light-duty vehicles**

**iLAST EURO PINK 50-50 PREDILUTED ANTIFREEZE/COOLANT** is an extended-life nitrite, amine, and phosphate (NAP) free OAT coolant formulated to provide superior performance for newer Audi, Volkswagen, Porsche, and other automotive and light-duty vehicles. As an initial fill and properly maintained, it provides extended-life 150,000 miles or 5 years of protection against rust, corrosion, and pitting for all coolant system metals. It meets or exceeds ASTM D3306, BS 6580, and VW TL774F performance levels and is fully compatible with similar formulated extended-life coolants. However, for the best results, do not mix with conventional high-pH, phosphate, borate, or silicate based coolants.

### Advantages

- Phosphate based Organic Acid Technology (OAT) coolant
- Extended Life 150,000 miles\* or 5 years of service protection
- Ethylene glycol based. Silicate, borate, nitrite and amine free
- Superior high-temperature aluminum protection
- Provides maximum protection against rust, corrosion, and pitting
- Blended with pure de-ionized water for your quality needs
- For safety purposes all iLAST antifreeze is blended with a bittering agent

### Specifications

iLast EURO PINK Antifreeze is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to): ASTM D3306, BS 6580, and VW TL774F.



V251121

## TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD	BOIL OVER PROTECTION		
Appearance	Visual	Pink/Purple	Type of Coolant Test	Atmospheric Pressure	15 LB cap
Specific Gravity at 60/60°F	1.065 - 1.080	ASTM D1122	Coolant Boiling	262°F	265°F
Freeze Point, at 50% max	-34°F	ASTM D3321	Cooling Freezing	-34°F	-34°F
pH at 50% Solution	7.8 - 9.0	ASTM D1287			
Reserve Alkalinity min.	1.5	ASTM D1121			
Foam volume (ml)	150ml/5 sec	ASTM D1881			

Available in Gallons, Drums, Totes, and Bulk.