

iLAST™ EXTENDED LIFE

EURO PINK Antifreeze/Coolant Concentrate

For use in Audi, Volkswagen, Porsche, and other automotive and light-duty vehicles

iLAST EURO PINK ANTIFREEZE/COOLANT CONCENTRATE is an extended-life nitrite, amine, and phosphate (NAP) free OAT coolant formulated to provide superior performance for newer Audi, Volkswagen, Porsche, and other automotive and light-duty vehicles. As an initial fill and properly maintained, it provides extended-life 150,000 miles or 5 years of protection against rust, corrosion, and pitting for all coolant system metals. It meets or exceeds ASTM D3306, BS 6580, and VW TL774F performance levels and is fully compatible with similar formulated extended-life coolants. However, for the best results, do not mix with conventional high-pH, phosphate, borate, or silicate based coolants.

Advantages

- Phosphate based Organic Acid Technology (OAT) coolant
- Extended Life 150,000 miles* or 5 years of service protection
- Ethylene glycol based. Silicate, borate, nitrite and amine free
- Superior high-temperature aluminum protection
- Provides maximum protection against rust, corrosion, and pitting
- For safety purposes all iLAST antifreeze is blended with a bittering agent

Specifications

iLast EURO PINK Antifreeze is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to): ASTM D3306, BS 6580, and VW TL774F.



V251121

TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Pink/Purple
Specific Gravity at 60/60°F	1.065 - 1.080	ASTM D1122
Freeze Point, at 50% max	-34°F	ASTM D3321
pH at 50% Solution	7.8 - 9.0	ASTM D1287
Reserve Alkalinity min.	1.5	ASTM D1121
Foam volume (ml)	150ml/5 sec	ASTM D1881

Available in Gallons, Drums, Totes, and Bulk.

FREEZE/BOIL PROTECTION CHART	% of Cooling System capacity		PROTECTS FROM	
	40	60	Freezing Down to	Boiling Up to*
Using a 15 PSI Pressure Cap	50	60	-10 °F	259 °F
	50	60	-34 °F	265 °F
	50	60	-62 °F	270 °F

Cooling System Capacity in Quarts	Quarts of Antifreeze Required for Protection to Temperature (°F) Shown										
	3	4	5	6	7	8	9	10	11		
8	-7	-34									
9	0	-21	-50								
10	4	-12	-34	-62							
11	8	-6	-23	-47							
12	10	0	-15	-34	-57						
13		3	-9	-25	-45						
14		6	-5	-18	-34	-54					
15		8	0	-12	-26	-43	-62				
16		10	2	-8	-19	-34	-52				
17			5	-4	-14	-27	-42	-58			
18			7	0	-10	-21	-34	-50	-62		
19			9	2	-7	-16	-28	-42	-56		
20			10	4	-3	-12	-22	-34	-48		

For best overall protection, solution strengths within the **YELLOW** color band are recommended.

50% SOLUTION RECOMMENDED TO OBTAIN MAXIMUM PROTECTION. DO NOT EXCEED 70% CONCENTRATION OF ANTIFREEZE.