

# iLAST™ EXTENDED LIFE

## Light Duty Gold 50/50 Antifreeze/Coolant

**iLAST LIGHT DUTY GOLD 50/50 ANTIFREEZE**, when used as directed, provides superior performance in virtually every light-duty application. The proprietary extended-life inhibitor package is low-silicate and phosphate and 2-EH free. It can be used as a top-off, but to achieve maximum protection, a complete flush and fill should be performed. iLast Light Duty Gold Antifreeze provides complete all-season protection against:

- Freeze-up
- Boil Over
- Scale Build Up
- Rusting
- Sludge/Clogging
- Corrosion

### Advantages

- Meets Light Duty ASTM D-3306
- Hybrid chemistry with long-life technology.
- Blended with pure de-ionized water for your quality needs.
- Recommended for use in all domestic and European models.
- Phosphate free and low silicate - the choice for Japanese and Korean models.
- Light Duty - 5 years/150,000 miles
- Compatible with any color antifreeze.
- For safety purposes all iLAST antifreeze is blended with a bittering agent.

### Specifications

iLast Light Duty Gold Antifreeze is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- JIS K 2234
- GM 1825M
- GM 1899M
- Chrysler MS 7170
- Ford ESE-M97B44-A



V251121

## TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD	BOIL OVER PROTECTION		
Appearance	Visual	Gold/Yellow	Type of Coolant Test	Atmospheric Pressure	15 LB cap
Specific Gravity at 60/60°F	1.053—1.083	ASTM D1122	Coolant Boiling	224°F	265°F
Freeze Point, at 50% max	-34°F	ASTM D3321	Cooling Freezing	-34°F	-34°F
pH at 50% Solution	8.5 - 10.0	ASTM D1287			
Reserve Alkalinity min.	2.5	ASTM D1121			
Foam volume (ml)	150ml/5 sec	ASTM D1881			

Available in Gallons, Drums, Totes, and Bulk.