

iLAST™ EXTENDED LIFE

MAXCOOL Orange 50/50 Antifreeze/Coolant

iLAST MAXCOOL 50/50 ANTIFREEZE/COOLANT, when used as directed, provides superior performance in light-duty applications - including light-duty trucks. The proprietary low-silicate inhibitor package is blended with advanced Hybrid Organic Technologies and is compatible with hybrid and OAT coolants - including Dexcool® Coolant. It is safe for all engine metals, including aluminum and can be used as a top-off, but to achieve maximum protection, a complete flush and fill should be performed. iLast MAXCOOL Antifreeze provides protection against:

- Freeze-up/Boil Over
- Scale Build Up
- Sludge/Clogging
- Wet Sleeve Liner Pitting
- Rusting
- Corrosion

Advantages

- Meets ASTM D-3306 and Long Life specifications.
- Safe for use with all engine metals, including aluminum.
- Light Duty Use - 150,000 miles.
- Compatible with hybrid and OAT coolants - including Dexcool®
- Safe for use with all engine metals, including aluminum.
- Suitable for American, European and Asian models.
- For safety purposes all iLAST antifreeze is blended with a bittering agent.
- Blended with pure de-ionized water for your quality needs.

Specifications

iLast MAXCOOL Orange Antifreeze is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- Chrysler MS 7170
- Ford WSS-M97B51-A1
- JIS K 2234
- TMC RP 302C
- Ford ESE-M97B44-A
- GM 6277M
- GM 1825M
- GM 1899M



V251121

TYPICAL PROPERTIES

DESCRIPTION	TYPICAL VALUES	TEST METHOD	BOIL OVER PROTECTION		
Appearance	Visual	Orange/Red	Type of Coolant Test	Atmospheric Pressure	15 LB cap
Specific Gravity at 60/60°F	1.053—1.083	ASTM D1122	Coolant Boiling	224°F	265°F
Freeze Point, at 50% max	-34°F	ASTM D3321	Cooling Freezing	-34°F	-34°F
pH at 50% Solution	8.5 - 10.0	ASTM D1287			
Reserve Alkalinity min.	2.5	ASTM D1121			
Foam volume (ml)	150ml/5 sec	ASTM D1881			

Available in Gallons, Drums, Totes, and Bulk.